

30 064 026 - 1



EnOcean plug-in adapter for series 64

FΩΔ64

Only skilled electricians may install this electrical equipment otherwise there is the risk of fire or electric shock!

Temperature at mounting location: See the operating instructions for the actuator of the series 64. Storage temperature: -25°C up to +70°C. Relative humidity: annual average value < 75%.

For flush mounting with series 64. 46x45 mm, 9 mm deep. EnOcean plug-in adapter for series 64.

With the EnOcean plug-in adapter, compatible EnOcean devices, such as the F2T55E or the F4T55E, can be paired with the series 64.


The ELTAKO Connect app is required for this. In addition, these EnOcean devices can be forwarded to various ecosystems via Matter.

ATTENTION: A series 64 actuator is required to which the adapter is plugged.

Installation instructions:

To ensure optimal reception properties, the EOA64 should be installed as far away as possible from metal components such as sockets or buttons.

The series 64 with the EOA64 should be installed in a switch box with the printing and terminals facing forward (see illustration). The EnOcean adapter EOA64 should be placed as deep as possible in the switch box. In this way, the maximum distance to sockets or buttons is achieved, which ensures optimal reception results.



Technical data

Additiona	l power consumption	+U.I W
Frequency	I	868.3 MHz

Manuals and documents in further languages:



https://eltako.com/redirect/EOA64





THE UNIQUE WIRELESS **PROFESSIONAL SMART HOME** STANDARD

Frequency	868.3 MHz
Transmit power	max. 10 mW

Hereby, ELTAKO GmbH declares that the radio equipment type EOA64 is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity can be accessed via the QR code or the internet address under 'Documents'.

Must be kept for later use!

ELTAKO GmbH

D-70736 Fellbach

Technical Support English:

+49 711 943 500 25

□ technical-support@eltako.de

eltako.com

08/2025 Subject to change without notice.