



Manuals and documents in further languages:  
[https://eltako.com/redirect/WSZ155DSS-16A\\_MID](https://eltako.com/redirect/WSZ155DSS-16A_MID)

Technical data page 10-29.

## WSZ155DSS-16A MID

**NEW** **MID**

**Mobile single-phase energy meter with German type plug and coupling (Type F). Suitable for indoor and outdoor use. Maximum current 16 A. Protection class IP54. Standby loss 0,4 watt only.**

Housing dimensions 155x60x82 mm, connection cable 1.5 m (including plug and coupling).

Accuracy class B (1%).

This mobile single-phase energy meter measures active energy by means of the current between input and output. The internal power consumption of 0.4 watt active power is neither metered nor indicated.

**The display changes cyclically every 10 seconds between the accumulated active energy in kWh and the instantaneous consumption in kWh.**

The start current is 20 mA.

The display can only be read when the power supply is on. However, the consumption is saved to a non-volatile memory and is displayed immediately after a power failure.

The digital display has 7 digits. Two decimal places are indicated up to 99999.99 kWh.

Above 100000.0 kWh there is only one decimal place.

The mobile single phase meter is equipped with a mounting bracket for easy installation. This can easily be removed if not necessary.

The power consumption is shown with a LED that flashes 2000 times per kWh.

<b>WSZ155DSS-16A MID</b>	Mobile single-phase energy meter, MID	<b>Art. No. 28016115</b>	<b>119,80 €/pc.</b>
--------------------------	---------------------------------------	--------------------------	---------------------